

390™

Electric Airless Sprayer



PROFESSIONAL ADVANTAGES

- Compact and Lightweight
- Easy to use
- Supports a 0.019" tip

MATERIALS

Lacquers - Acrylic - Primers - Enamels - Varnishes - Thin acrylic paints

Painter - Fine Finish & Professional Airless Applications

390™



390™

Electric Airless Sprayer



Ready to Spray
Delivered complete with FTx™ gun, RAC X™ tip & guard, and a BlueMax™ hose.



Offset Handle with Comfort Grip
• Unit is balanced away from your body for easy transport



Endurance™ Pump
• Chromex™ Rod and Hardened Stainless Steel cylinder
• NEW QuickAcces intake valve:
- requires only a hammer to access the intake ball
- easy to clean or clear debris

NEW

Lightweight Design
• Graco's lightest professional sprayer at only 14 kg
• Easy to lift and carry

Welded Steel Frame
• Four-leg design for solid footing
• Rugged leg caps to protect floor

Consistent Pressure Control
• Delivers quality spray pattern with minimum fluctuation

Big Cup
• Holds inlet tube
• Prevents drips during transport



Swivel Inlet Suction Hose
• Easily swivels to reach buckets or cans



390™

390™ Advanced Features

ACCESSORIES

Guns

- 288438 FTX-E Gun with RAC X 517 tip, RAC X guard and 2 filters
- 288428 FTX-E Gun with RAC 5 guard, no tip

Easy Out™ Gun Filters

- 287032 PRO Easy Out gun filter, 60 Mesh x 1
- 287033 PRO Easy Out gun filter, 100 Mesh x 1

Easy Out Pump Filters

- 246425 30 Mesh, grey
- 246384 60 Mesh, black
- 246382 100 Mesh, blue
- 246383 200 Mesh, red

Pro Tip Extensions

- with RAC X Guard
- 287019 25 cm
- 287020 40 cm
- 287021 50 cm
- 287022 75 cm

Roller Kits

- 245397 Roller Kit (Int.)
- 244281 Telescopic Roller

Tips & Guards

- FFAXXX RAC X Fine Finish Tip
- PAAXXX RAC X Professional Airless Tip
- 262XXX RAC 5 Tip
- 246215 RAC X Guard
- 243161 RAC 5 Guard

Liquids

- 206994 TSL™ 0.25 l
- 243103 Pump Armor™ 1 l

SPECIFICATIONS

390™	
Stand Mount	
Part Numbers:	
for Europe - 220 V	254968
for Italy, Switzerland, Denmark - 220 V	254969
for UK - 110 V	253961
Max. Tip Size	0,019"
Max. Fluid Flow	1.8 l/min.
Max. Pressure	225 bar
Weight	14 kg
Motor type	Open frame DC
Motor rating	(1/2 HP) 0.4 kW

Unit ships complete with: FTx™-E gun, BlueMax™ hose 1/4" x 15 m, RAC X tip 517, HandTite™ guard and pressure gauge.

Find this unit at: